

HARTUNG

GLASS INDUSTRIES

www.hartung-glass.com / info@hartung-glass.com

Ph: 1-800-552-2227 / Fax: 425-656-2601

Total Vision System Worksheet

| | |
|----------------|-----------------|
| Date: | Quote Due Date: |
| Contact Name: | Company Name: |
| Project Name: | City/State: |
| Phone Number: | Fax: |
| Email Address: | |

Glass Thickness

3/8" (10mm) 1/2" (12mm) 3/4" (19mm)

Glass Type

Clear Low Iron Satin Etch

Bronze Gray Other _____

Door Type

P A/F BP INV BP

Finish

US28 Satin Anodized

313 Dark Bronze Anodized

US32 Polished SIS

US32D Brushed SIS

Painted: _____

Other: _____

Top

Patch Fitting

4" Corner Patch Rail

Door Rail - Full Length

Bottom

Patch Fitting

4" Corner Patch Rail

Door Rail - Full Length

If Using Door Rail

Square Style: 2-5/16" 4" 6" 10"

Taper Style: 4"

Aluminum Header

Yes No

Continuous w/ Pocket

ANODIZED

1-3/4" x 4"

1-3/4" x 4-1/2"

CLAD

1-7/8" x 4-3/16"

1-7/8" x 4-11/16"

Closer

Yes No

Overhead Concealed

Concealed Floor

Hold Open 90° 105°

No Hold Open 90° 105°

Door Pull

Yes No

10" Back-to-Back D-Pull

12" Back-to-Back D-Pull

Ladder Pull - Length _____

Other: _____

Panic Handle

PA DB DH

Exterior Handle

A F Other _____

Other: _____

Manual Strike Electric Strike

Locks

Yes No

Keyed Cylinder

Thumb Turn

Dummy Cylinder

IC Housing/Core

Center Lock

Surface Magnetic Lock

SDC 1562 Shear Magnetic Lock

GF3000 Shear Magnetic Lock

Power Supply

Dust Proof Strikes

Yes No Quantity: _____

Sidelite Rail & Accessories

Header with Glass Pockets

1-5/8" x 1-5/8" U-Channel

1-5/8" x 3/4" U-Channel

Wet Glaze: 1" 1.5" 2"

Sidelite Rail: Top Bottom

Square Style: 2-5/16" 4" 6" 10"

Taper Style: 4"

Jambs: Yes No

Seals: Yes No

Drawings & Notes

Please use the space below or attach a separate sheet.