

HARTUNG

GLASS INDUSTRIES

www.hartung-glass.com / unioncity@hartung-glass.com

Ph: 1-800-479-2992 / Fax: 510-487-1145

Total Vision System Worksheet

Date:	Quote Due Date:
Contact Name:	Company Name:
Project Name:	City/State:
Phone Number:	Fax:
Email Address:	

Glass Thickness

3/8" (10mm) 1/2" (12mm) 3/4" (19mm)

Glass Type

Clear Low Iron Satin Etch

Bronze Gray Other _____

Door Type

P A/F BP INV BP Other _____

Finish

US28 Satin Anodized

313 Dark Bronze Anodized

US32 Polished SIS

US32D Brushed SIS

Painted: _____

Other: _____

Top

Patch Fitting

4" Corner Patch Rail

Door Rail - Full Length

Bottom

Patch Fitting

4" Corner Patch Rail

Door Rail - Full Length

If Using Door Rail

Square Style: 2-5/16" 4" 6" 10"

Taper Style: 4" Other _____

Aluminum Header

Yes No

Continuous w/ Pocket

ANODIZED

1-3/4" x 4"

1-3/4" x 4-1/2"

CLAD

1-7/8" x 4-3/16"

1-7/8" x 4-11/16"

Closer

Yes No

Overhead Concealed

Concealed Floor

Hold Open 90° 105°

No Hold Open 90° 105°

Door Pull

Yes No

10" Back-to-Back D-Pull

12" Back-to-Back D-Pull

Ladder Pull - Length _____

Other: _____

Panic Handle

PA DB DH

Exterior Handle

A F Other _____

Other: _____

Manual Strike Electric Strike

Locks

Yes No

Keyed Cylinder

Thumb Turn

Dummy Cylinder

IC Housing/Core

Center Lock

Surface Magnetic Lock

SDC 1562 Shear Magnetic Lock

GF3000 Shear Magnetic Lock

Power Supply

Dust Proof Strikes

Yes No Quantity: _____

Sidelite Rail & Accessories

Header with Glass Pockets

1-5/8" x 1-5/8" U-Channel

1-5/8" x 3/4" U-Channel

Wet Glaze: 1" 1.5" 2"

Sidelite Rail: Top Bottom

Square Style: 2-5/16" 4" 6" 10"

Taper Style: 4" Other _____

Jambs: Yes No

Seals: Yes No

Drawings & Notes

Please use the space below or attach a separate sheet.