

ANNOUNCING NEW PANELGRIP® DRY GLAZE SYSTEM



PANELGRIP® DRY GLAZE SYSTEM

THE LATEST IN GLASS RAILING TECHNOLOGY.

PanelGrip® facilitates the quick assembly of structural glass railing without messy fillers or special tools. The patented PanelGrip® Dry Glaze Railing System results in significant savings in labor and shipping costs while providing a safe, strong guard rail that meets the most stringent building codes.

PRODUCT FEATURES

Reduce Labor Costs up to 80%

No sealing of shoe, no setting blocks, no plumbing of glass, no multiple pours of cement, no waiting for cement to cure, no messy clean up.

No Special Tools

All you need is an Allen wrench for installation or removal.

No Mess

No mixing and pouring of expansion cement, no running of cement on incline.

Reduce Freight Costs up to 30%

PanelGrip® base shoe is 30% lighter than standard base shoes yet meets structural load requirement for railings.

Broadest Grip Range of Any Dry Glaze System

Made for 1/2", 3/4", 13/16" (12.7mm, 19mm, 21mm) tempered and laminated glass.



Aluminum Base Shoe




PanelGrip Dry Glaze System

RAPID INSTALLATION


PANELGRIP® DRY GLAZE SYSTEM

The PanelGrip® dry glaze railing consists of two main components; base shoe & the patented PanelGrip® isolator. It can be mounted to a variety of substrates and is compatible with a wide variety of cladding, top rail, hand rail and accessories.




ALUMINUM BASE SHOE

PanelGrip® Base Shoe is extruded from 6005-T5 in mill finish. Stocked in: 10' & 20' lengths. Made for range of 1/2" to 13/16" tempered and laminate glass. CB, SD & Undrilled.




ISOLATORS

The patented PanelGrip® System utilizes a unique locking mechanism of high-strength aluminum and PVC isolators combined with a specially designed aluminum shoe moulding. Isolator assembly is adjustable to accommodate 1/2" through 13/16" glass. Glass Deduction = 15/16". 10ft/lbs of torque.



SHOP DRAWINGS & ENGINEERING AVAILABLE




Part #	Base Section	Glass Size(T)	Color
A42-0028-1B	A42-0073	.520" - .560"	Black
A42-0028-1W	A42-0073	.775" - .820"	White
A42-0028_1R	A42-0073	.830" - .865"	Red
A42-0027-1L	A42-0072	.465" - .560"	Brown


PRODUCT DETAILS:

- Simple To Install on an Incline
- Can Be Installed Completely From One Side
- Stocked In 10' & 20' Stock Lengths
- Bottom Fascia Mount Drilling Available
- Cladding & Top Rail Available
- Drain Blocks and Weld Blocks available
- Custom engineering and shop drawings available

The PanelGrip® base shoe and mechanism are sold as a system and are subject to one or more of the following patents: US7730682, US8181405, NZ581456, CA2697162, EP2171180 and/or AU2008282693



PanelGrip® Isolator




ALSO AVAILABLE:



Single Standoffs



Double Standoffs



Post & Clamp Systems



Square & Round Clamps